

## Models 880/1080/1280 Ka-Band Mobile VSAT IP Broadband Antenna Systems

- Key Features**
- Highly Efficient Motorized Antennas
  - Zero Backlash AvL Cable Drive
  - Auto-Acquisition Controller

**Standard Feed** Commercial Ka-band (optional Ku-band)  
**Reflector Sizes (Model)** 85cm (880), 1.0m (1080) or 1.2m (1280)

- Configurations**
- Vehicle-Mount
  - Fly&Drive
  - FlyAway – Case-Based or Tripod
- Market Solutions**
- Mobile Broadband Internet Access
  - Satellite News Gathering
  - Disaster Relief
  - Oil & Gas Data Backhaul
  - Defense & Homeland Security

- Operates With**
- ViaSat / exede
  - Eutelsat / tooway
  - Avanti / HYLAS
  - HughesNet



### Mechanical

Az/El Drive	Motorized AvL Zero Backlash Cable Drive (Patent Pending)		
Polarization	RHCP/LHCP Pol Select Option Available		
Reflector Construction	Single Piece Carbon Fiber		
Axis Travel	Azimuth	400° (±200°)	
	Elevation	0-90° antenna boresight (true elevation from calibrated inclinometer)	
Az/El Speed	Slewing/Deploying	Typical: Elevation 0.1°/second, Azimuth 2°/second	
Motors	24 VDC Variable Speed, Constant Torque		
Interface	Type F connector(s) at antenna base or 25 ft. (7.6m) Coax from Base		
Electrical Interface	One 25 ft. (7.6m) cable with connector from base connector panel to controller		
Manual/Emergency Drive	Handcrank for az and el axes		
Time to Acquisition	Less than 15 minutes; 8 minutes typical		
Stowed Dimensions	<u>85cm Antenna (880)</u>	<u>1.0m Antenna (1080)</u>	<u>1.2m Antenna (1280)</u>
	53 L x 36 W x 13½ H inches (135 L x 91 W x 34 H cm)	61.5 L x 40 W x 15 H inches (156 L x 102 W x 38 H cm)	69 L x 48 W x 16.3 H inches (174 L x 122 W x 41 H cm)
Weight (approximate – depends on options selected)	90 lbs. (41 kg) typical	111 lbs. (50 kg) typical	130 lbs. (59 kg) typical

### Environmental

Wind – Survival	Deployed	<u>85cm Antenna (880)</u>	<u>1.0m Antenna (1080)</u>	<u>1.2m Antenna (1280)</u>
	Stowed	80 mph (129 kph ) 100 mph (161 kph)	80 mph (129 kph ) 100 mph (161 kph)	80 mph (129 kph ) 100 mph (161 kph)
Wind – Operational		45 mph (72 kph)	45 mph (72 kph)	45 mph (72 kph)
Pointing Loss in Wind - Ka (Rx) 30 mph gusting to 45 mph (48 kph gusting to 72 kph)		1.0 dB typical	1.0 dB typical	1.0 dB typical
Temperature:	Operational	-25° to 125° F (-32° to 52° C)	-25° to 125° F (-32° to 52° C)	+5° to 125° F (-15° to 52° C)
	Survival	-40° to 140° F (-40° to 60° C)	-40° to 140° F (-40° to 60° C)	-40° to 140° F (-40° to 60° C)

# AVL TECHNOLOGIES

## Ka-Band Mobile VSAT IP Broadband Antenna Family

RF/Electrical						
Reflector Size ►	85 cm (Model 880)		1.0m (Model 1080)		1.2m (Model 1280)	
RF Parameter ▼	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency Range (GHz)	19.7 - 20.20	29.5 - 30.0	19.7 - 20.20	29.5 - 30.0	19.7 - 20.20	29.5 - 30.0
Polarization Configuration	RHCP or LHCP		RHCP or LHCP		RHCP or LHCP	
Gain (mid-band) @ Horn Interface (dBi)	43.1	46.6	44.5	48.0	46.1	49.6
G/T (mid-band, clear horizon) assuming 100 K LNB (dB/K)	19.8		21.2		22.8	
Beamwidth (degrees) -3 dB	1.2	0.8	1.1	0.7	0.9	0.6
-10 dB	2.3	1.5	1.9	1.3	1.6	1.1
Radiation Pattern Compliance	ITU-R S.580.6		ITU-R S.580.6		FCC 25.209, ITU-R S.580.6	
Antenna Noise Temperature (midband)	109 K		107 K		107 K	
Power Handling Capability		50W		50W		50W
VSWR @ Horn Interface	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Reflector Optics	0.7 f/D		0.8 f/D		0.8 f/D	
Feed Type	Integral Feed/ Polarizer/OMT/Transceiver		Integral Feed/ Polarizer/OMT/Transceiver		Integral Feed/ Polarizer/OMT/Transceiver	
Axial Ratio	Feed Dependent		Feed Dependent		Feed Dependent	
Cross-Polarization Isolation	Feed Dependent		Feed Dependent		Feed Dependent	
Feed Port Isolation – Tx to Rx	Feed Dependent		Feed Dependent		Feed Dependent	

## Controller

Controller Type ►	Auto-Acquire/Jog Control & Display with Auto-Stow
Standard Features	Fully Automatic Satellite Acquisition and Peaking with GPS, Compass, Level Inputs and auto compensation with Entry of Desired Satellite. Select 10"x9"x2.5" power supply/hand-held controller or 1 RU P.S. controller.
Positioning Accuracy	±0.2°
Input Power	95-250VAC auto-ranging, 50/60 Hz, 6/3 A peak, 1 A continuous

## Available Options, Upgrades & Services

- Upgrade to Custom RF/IF I/O cabling configurations available
- 2-Port Ku-band Feed
- Custom Colorization (contact factory for available colors)
- Add Custom Logo on Reflector Face (1- or 2-Color; per AvL Logo Policy)
- Spare Parts Kit